

EN

# Composite Bracket

## KEY FEATURES

- Rust free – ideal where there is salty sea air
- 80kg maximum load
- Adjustable with 3 fixing points
- Fixing kit supplied
- Fast, easy 'snap on' leg assembly



# Galvanised Arm

## KEY FEATURES

- Industrial 41mm x 41mm channel
- Base of 130mm x 45mm
- 14mm diameter holes at 100mm centres
- 600mm length available



### SPECIFICATIONS

|  |   |
|--|---|
| Composite Bracket<br>Materials of construction | Bracket: fibre reinforced nylon<br>Crossbar: glass reinforced polyester |
| Galvanised Arm<br>Materials of construction    | Mild steel hot dipped galvanised  |

### SIZING OPTIONS

| Description              | Max. Load | Height (mm) | Width (mm) | Depth (mm) | Part No. |
|--------------------------|-----------|-------------|------------|------------|----------|
| Composite Bracket Type 1 | 80kg      | 410         | -          | 460        | B6760    |
| Composite Bracket Type 2 | 80kg      | 410         | 790        | 460        | B6761    |
| Galvanised Arm 600       | 183kg**   | 132         | -          | 600        | B6860    |

\* Point load 119kg  
\*\* Point load 92kg

For further details please refer to our website [aspenspumps.com](http://aspenspumps.com)

Information correct at time of going to press.