



CONDENSATE REMOVAL PUMP

The Macerator pump efficiently handles condensate and defrost water from multiple refrigeration units, and will deliver reliable, quiet performance in high-demand commercial environments.



780L/h max. flow



8.5m max. rec. head (flow rate 80L/h)

Key Features

- Internal filter blade
- High flow & head
- High level safety switch


Suitability

- Single and multiple refrigeration units
- Perfect for... handling food waste that may pass through the pump



5.2 kg			270mm
~	305mm	← 152mm →	

MACERATOR 4L @ 230 VAC 50-60HZ		
Max. flow	780L/h	
Max. rec. head	8.5m	
Tank capacity	4L	
Sound level@1m	64dB(A)	
Power supply	230VAC, 50Hz, 1.1A	
Rated	Continuous	
Class	I appliance	
Max. ambient temp	40°C/104°F	
Max. water temp	40°C/104°F	
Inlet/outlet	40mm in,10mm out	
IP Protection	IP20	
Safety switch	5.0A Normally closed	



MACERATOR 4L OPTIONS		
Macerator 4L	FP2305/3	

SUGGESTED	XTRA ACCESSOR	RIES
Description		Part No.
Vinyl Tube Braided 3/8" (10mm)	†	AX5101
V In A	illation accessorie spen Xtra range	es take

IN THE BOX
Macerator 4L pump • Hard wired 2m power cable • Install manual

Download manual at aspenpumps.com