



Maxi Orange

CONDENSATE REMOVAL PUMP

Need more performance? Designed for larger units, the Maxi Orange pump gives you the extra power when you need it.



35L/h max. flow

15m max. rec. head (flow rate 10L/h)


35dB(A) @ 1 m


Key Features


- High power motor
- Superior performance
- Submersible secondary reservoir included


Suitability

- Up to 46kW / 157 000 Btu/h
- High wall split systems; Ducted units; Floor standing & Chassis units
- Perfect for... Large commercial units









230 VAC 50Hz			
Max. flow	35L/h @ 0m head		
Max. rec. head	15m		
Max. suction lift	2m		
dB(A) @ 1m	35dB(A)		
Power supply	230 VAC, 50-60Hz, 0.11A, 16W		
Rated	Non continuous		
Class	II 🗖		
Max. unit output	46kW (157,000 Btu/h)		
Max. water temp	40°C (104°F)		
Discharge tube	6mm ID		
P Protection	IP21		
Safety switch	3.0A Normally closed		
Thermal protection	1		

Fully potted Self priming

18

OPTIONS			
Maxi Orange		FP2210	
⁺ Pump only			
SUGGESTED XTRA ACCESSORIES			
Description		Part No.	
1 Amp Fuse		FP2620	
Tube To Soil Stack Adaptor		FP2038	

Vinyl Tube Braided 1/4" (6mm)



Visit aspenpumps.com for more installation accessories.

AX5100

IN THE BOX Maxi Orange pump • 1.5m Plug & Play power cable • Reservoir • Reservoir lid with 1.5m sensor cable • Submersible reservoir • Anti siphon device • Float & filter • 1.5m Suction tube 6mm ID •

Float & filter • 1.5m Suction tube 6mm ID •
220mm Orange inlet hose
14mm ID • 150mm Vinyl breather tube 6mm ID

Drain connector kit • Fixing kit • Install manual

Download manual at aspenpumps.com

Watch installation video at aspenpumps.com

Information correct at time of going to press. Not all products are available in all regions.